

# glass tiles

## Technical data sheet

### Product description

Glass tiles made of frost-proof quality glass, optionally super white glass, with colored enamel on the back, incl. a white top layer, not solid-colored. The surface is generally glossy; optionally frosted for a few colors. The product can be supplied in various formats, thicknesses, colors and surface refinements; color gradients are possible.

### Areas of application

#### Interior

- As wall and ceiling cladding
- As swimming pool lining in private houses

#### Exterior/facades

- As exterior wall and ceiling cladding on massive ground
- As cladding on suspended, rear-ventilated plaster support systems

### Color batches/samples

Delta Elements sorts the products according to the hues or color mixtures specified on the respective cartons. Only glass mosaic of one order color batch must be used to avoid large color differences; waste material is to be calculated. Small color differences up to a Delta E amount of 3,0 are possible within one order unit. The hues are generally based on 8 mm standard glass thickness; with a thickness of 6 mm, the hue can deviate due to the coloring.

Samples are principled non-binding and can deviate from the hue of the ordered goods for production technology reasons. This concerns particularly the color batch, adhesive foil, wrapping and others.

### Technical specifications

Frost resistance	ISO 10545-12	in accordance
Water absorption	ISO 10545-3	< 0,5%
Resistance to temperature fluctuations	ISO 10545-9	in accordance
Resistance to chemicals	ISO 10545-13	in accordance
Light resistance of the colors	DIN 51094	in accordance
Thermal shock resistance	ANSI A 137.2-2012	in accordance

**Processing/storage**

The product has to be processed by the floating-method (glue on one side) according to DIN EN 12004. Full-surface adhesion of the product is essential. The optimum processing temperature is between 5 and 30° C. The product has to be stored implicit dry, in the shade, dust- and frost-proof and has to be processed within 6 months after production date.

You can find the detailed Delta Elements processing instructions as PDF download at our website (under "glass tiles" product section): [www.deltaelements.eu](http://www.deltaelements.eu)

**Customer service**

Tel. +49 69 8570125-0  
[info@deltaelements.eu](mailto:info@deltaelements.eu)

**Delta Elements GmbH**

Bernardstraße 14-16  
63067 Offenbach/Main  
Germany  
Tel. +49 69 8570125-0  
Fax +49 69 8570125-1  
[info@deltaelements.eu](mailto:info@deltaelements.eu)  
[www.deltaelements.eu](http://www.deltaelements.eu)

---

This technical data sheet replaces the previous version. It provides information about the product properties and fields of application. Delta Elements has compiled all recommendations with due diligence according to the state of the art. Numeric information may deviate within the general tolerances for production technology reasons. The list of standards and directives merely serves as an overview with no claim of completeness. This technical datasheet does not constitute any guarantee in regard to the recommendations provided. Delta Elements assumes no liability and refers to its general business terms and conditions. No rights can be derived from the contents of the technical datasheet. The respective current version and the general business terms and conditions are available at [www.deltaelements.eu](http://www.deltaelements.eu); printing errors reserved.

---